Easiway Dip Tank and Emulsion Remover Cheat Sheet

Mix ratios and dwell times for EasiStrip, Supra, 1028, EasiSolv 5 and 55, and Screen Perfect degreaser.

Mix ratios (chemical : water)

Product	Ratio	Time on screen	Use
EasiStrip	1 : 2	30 s - 1 min dip	Plastisol ink + emulsion, dip tank
EasiStrip Supra	1 : 7	30 s - 1 min dip	Plastisol and water-based, dip tank
EasiSolv 1028	Ready to use	brush/spray, then rinse	UV/solvent, conductive, industrial
EasiSolv 5	1 : 10 to 1 : 50	about 1 minute	Stencil remover
EasiSolv 55	1 : 30 to 1 : 55	apply, then rinse	Stencil remover concentrate
Screen Perfect	1 : 20	before coating	Degreaser; pinholes and fish eyes

Dip tank sizes (Easiway)

PT 506	14 gallons
PT 525	25 gallons
PT 520	37 gallons
UNI 50	50 gallons

After the dip or stencil remover

Rinse	High pressure both sides, then low pressure flood rinse
Stains	EasiSolv 701N, 415N, 400 or GOLD

Sources: Easiway technical data sheets for EasiStrip, EasiStrip Supra, EasiSolv 1028, 5, 55, Screen Perfect; maker list dip tank capacities. Reference only: Easiway's current technical data sheet and SDS govern.