Tekmar Spot Cleaning Fluids and Guns

TS-1, TS-3, TS-5, DT-1000 and Premium 2000 fluids plus TG125, TG200, TG300 and TG350 spot guns, from Tekmar's pages and flyers.

Spot cleaning fluids

Fluid	Removes (Tekmar)	Notes (Tekmar)
Formula TS-1	Grease, oil, dirt, marking pencil, lipstick, cosmetics	Spotter 'safe on virtually all fabrics including silks and satins'; contains Teknaklean additive; non-flammable, instant drying, non-ringing, low odor
Formula TS-3	100% of cured plastisol inks; water-based, puff and flock adhesives; flock lettering and transfers; grease and oil	Used in all cleaning guns; non-staining gun lubricant; Teknaklean additive; non-flammable, instant drying, non-ringing, low odor
Formula TS-5	Screen printing inks and adhesives; grease, oil, dirt, cosmetics; other industrial and household stains	No methylene chloride, N-propyl bromide or perchloroethylene; no detectable flash point; not Prop 65 listed; EPA SNAP approved; non-hazardous for shipping
Formula DT-1000	DTG inks and DTF transfers (dissolves virtually all inks and adhesives used in DTG and DTF)	Sprayed through a spot cleaning gun; same no-methylene-chloride, no-flash-point profile as TS-5
Formula Premium 2000	Grease, oil, dirt, cosmetics; many industrial and household stains; all textile fabrics and porous material	Hand spotter or conventional spot cleaning equipment; TLV in excess of 200 ppm; not a flammable liquid; non-hazardous for shipping

Spot cleaning guns

Gun	Facts (Tekmar)	Item numbers
TG200 MK II	Aluminum case with double ground electrical protection; high output silicone oscillation motor; 'old faithful' all-metal classic	110V TG200; 220-240V TG200-220
TG300 PRO	Exclusive bronze alloy pump; fiberglass-reinforced styrene handle; ergonomic; extra-wide container	110V TG300; 220-240V TG300-220
TG350 Pro Series	Heavy-duty air-cooled 50 W motor; fluid-saving high output pump; integrated air dryer with side trigger; large reservoir; no maintenance	110V TG350; 220/240V TG350-220
TG125	Affordable; fully adjustable nozzle for delicate fabrics; accepts Direct Feed and Air Dryer	110V TG125; 220-240V TG125-220

Safety and station

Read the SDS	Wear protective gear; check handling before use
Exhaustex 2000	Over 500 CFM vacuum, refillable carbon filter, stainless chemical shield, inspection lamp
Warranty (guns)	Lifetime limited: parts 12 months, labor for the working life

Sources: tekmarltd.com product pages (2026-11-19) and Tekmar Spot Guns flyer (2019). Fluid sizes: 1 gal, 5 gal, 55 gal drums. Hazard statements are Tekmar's; the SDS governs.