TECHNICAL DATA SHEET

EASISOLV 120

ON PRESS CLEANER

EASIWAY

EasiSolv 120 On Press Cleaner is designed to remove all inks from the screen printing mesh. This product evaporates quickly and should not be rinsed with water. 120 is to be used during on press color changes, saved screens, removing ink from squeegees, floodbars and other equipment.

Appearance:	Clear
Odor:	Ether-like
Ph:	Neutral
Flash Point:	48°C / 118°F
Specific Gravity:	0.95 @ 20°C / 68°F
Weight/gl:	Not Applicable
VOCs:	950 grams/liter
Dot Shipping:	Non-hazardous

Quart	120-1 QT
Gallon	120-1 GL
5 Gallon pail	120-5 GL
55 Gallon Drum	120-55 GL

STORAGE REQUIREMENTS

Keep the container tightly closed. Store in a dry, cool and well ventilated place away from incompatible materials such as oxidizing agents and acids.

PRODUCT FEATURES

- Low flash point
- Quick evaporation
- Good adhesive remover
- Non-hazardous
- Low to no odor

APPLICATION/USE

Scrape all excess ink from screen. Apply EasiSolv 120 by squirt bottle, pneumatic sprayer or by rag to the ink side of the screen. Thoroughly agitate ink with a rag or scrubber, then wipe up all dissolved ink. Reapply if necessary and follow with a dry rag, wipe on both sides of the screen. The screen will be ready for printing or tape application within 20 seconds.

COMPATIBLE INK TYPES

- Plastisol
- Waterbased
- Solder Mask
- Pad Inks
- Industrial
- UV
- Solvent