TECHNICAL DATA SHEET

EASISOLV 401N

SQUEEGEE & FLOODBAR WASH

Easisolv 401N Squeegee and Floodbar Wash, the first of its kind, represents a significant leap forward in innovation. Easisolv 401N does not swell squeegee rubber, ensuring prolonged equipment lifespan and consistent printing quality. Its unique formula is designed specifically for use in automated cleaning equipment, streamlining operations and enhancing efficiency like never before.

Appearance:	Clear, Water White
Odor:	Mild Solvent
Ph:	Neutral
Flash Point:	> 93°C / 200°F
Specific Gravity:	0.80 @ 20°C / 68°F
Weight/gl:	6.4 lbs/gallon
VOCs:	652 g/l (5.4 lbs/gal)
Dot Shipping:	Non-hazardous

Gallon	401N-1 GL
5 Gallon pail	401N-5 GL
55 Gallon Drum	401N-55 GL

COMPATIBLE INK TYPES

- Plastisol
- Solvent
- UV

STORAGE REQUIREMENTS

Store in well-ventilated place. Keep cool. Store in closed container. Dispose of contents/container in accordance with local/regional/federal regulations.

PRODUCT FEATURES

- High Flash Point
- Non-Flammable
- Can be used in a parts washer
- Will not swell squeegee rubber
- Takes ink out of suspension
- Restricted Substances List Compliant (Nike, Gildan, Adidas)

APPLICATION/USE

Manual Application:

- Scrape excess ink from squeegees, flood bars, and tools.
- Apply 401N on a rag
- Wipe down squeegee, flood bars, and tools.
- Allow to dry.

Machine Application:

- Initial fill should be 1 part 401N to 2 parts water.
- Scrape excess ink from squeegees, flood bars, and tools.
- Load into machine and run at prescribed cycle time.
- Unload tools, wipe excess liquid off and allow to dry.