TECHNICAL DATA SHEET

# EASISOLV 5
## STENCIL REMOVER

EASIWAY

EasiSolv 5 Stencil Remover is a non-hazardous, liquid, concentrated solution with addatives designed to aggressively dissolve direct, direct/indirect emulsions, as well as capillary films. Mixes with water up to 1:4. When rinsed with high pressure water emulsion and capillary films will be easily removed.

| | |
|---|---|
| ***Appearance:*** | Clear, light yellow |
| ***Odor:*** | Mild |
| ***Ph:*** | 2-4 |
| ***Flash Point:*** | Not Applicable |
| ***Specific Gravity:*** | 1.05 @ 20°C / 68°F |
| ***Weight/gl:*** | Not Applicable |
| ***VOCs:*** | None |
| ***Dot Shipping:*** | Non-hazardous |

| | |
|---|---|
| ***Quart*** | 5-1 QT |
| ***Gallon*** | 5-1 GL |
| ***5 Gallon pail*** | 5-5 GL |
| ***55 Gallon Drum*** | 5-55 GL |

### STORAGE REQUIREMENTS

Keep the container tightly closed. Store in a dry, cool and well ventilated place away from incompatible materials such as caustics.

### PRODUCT FEATURES

- Drain safe when mixed with water
- Zero VOCs
- Dissolves virtually all films and emulsions from coarse and fine mesh
- Degreases as it dissolves stencils

### APPLICATION/USE

After ink has been removed from the screen, mix EasiSolv 5 from 1 part chemical to 10 parts water (up to 1 part chemical to 50 parts water). Apply by brush, wipe, scrub pad, or spray to both sides of the emulsion and scrub. Let sit for a minute and then high pressure rinse both sides of the screen. Flood rinse the entire screen with a low-pressure rinse from the top to remove any debris, splashback, and chemical residue.

### COMPATIBLE INK TYPES

- Plastisol
- Waterbased
- Silicone
- UV/Solvent
- Conductive
- Industrial