TECHNICAL DATA SHEET

PLASTISOLV 800

ON PRESS CLEANER

EASIWAY

PlastiSolv 800 On Press Cleaner is used for cleaning off screens during on press color changes or for saved screens. Excellent for removing ink from squeegees, floodbars, and other equipment. PlastiSolv 800 evaporates quickly and leaves no residue.

Appearance:	Clear
Odor:	Citrus
Ph:	Neutral
Flash Point:	62°C / 110°F
Specific Gravity:	0.79 @ 20°C / 68°F
Weight/gl:	6.4 lbs/gallon
VOCs:	790 grams/liter
Dot Shipping:	Non-hazardous

Quart	
Gallon	800-1 GL
5 Gallon pail	800-5 GL
55 Gallon Drum	800-55 GL

STORAGE REQUIREMENTS

Keep the container tightly closed. Store in a dry, cool and well ventilated place away from incompatible materials such as oxidizing agents and acids.

PRODUCT FEATURES

- Citrus odor, making reclaiming pleasant
- WIll not “lock in” emulsions and films
- Non-flammable
- Can be applied manually or recirculated through EasiFlo System, or in enclosed automatic screen rewashing system

APPLICATION/USE

Scrape excess ink from the screen. Apply PlastiSolv 800 by squirt bottle, pneumatic sprayer, or rag to the (well) ink side of the screen. Thoroughly agitate ink with a rag or a scrubber, then wipe up all the dissolved ink with a shop rag on both sides. The screen will be ready for printing or tape application within 10-15 seconds.

COMPATIBLE INK TYPES

- Plastisol