PIF 01633

PC-175

PRESS WASH & SCREEN IMAGE OPENER

WORKS ON **8** INK TYPES · PLASTISOL TO UV

Use as supplied | Solvent blend | Citrus odor

Textile Printing | Graphics Printing | Manual

DESCRIPTION

PC-175 is a powerful, fast-acting press wash and screen image opener for press-side wash-up, on-press color changes, equipment clean-up, adhesive removal and screen reclaim prep. It works on plastisol, conventional, solvent, UV, vinyl, enamel, epoxy and water-based inks. PC-175 also removes vinyl adhesive and leaves no residue behind.

ADVANTAGES

Works on Graphic & Textile Inks
Plastisol, UV, solvent, water-based, epoxy, vinyl

Removes Vinyl Adhesive
Also cleans equipment and lifts adhesive

Emulsion & Mesh Safe
Opens images on press without harming the stencil

No Residue
High solvency; wipes clean so printing can resume

DIRECTIONS

- Spray or wipe the affected area on the ink side of the screen, as supplied.
- Keep wiping, turning the towel often, until the area is dry.
- Before resuming printing, test print on scrap material to make sure all residue is gone.
- Use before screen reclaim to remove ink from the screen.
- Use in a well-ventilated area away from heat, sparks and flame. Ground and bond containers when transferring from drums or pails.



55 gal drum
01633-D5505



5 gal pail
01633-P5010



1 gal · 4 × 1 gal
B1201 · C4201



12 × 1 qt
01633-C3004

COST PER SCREEN

FL OZ PER SCREEN	SCREENS PER GAL	SCREENS PER DRUM	COST PER SCREEN
0.125 fl oz	1,024	56,320	$0.05
0.25 fl oz	512	28,160	$0.09
0.5 fl oz (reference)	256	14,080	$0.19

Reference use: 0.5 fl oz per screen, about 15 trigger sprays at 1 ml per spray, for $0.19 per screen. Cost = fl oz used × $0.38 per fl oz ($48.17/gal, 55 gal drum MSRP, effective July 3, 2026). Actual use varies with screen size and ink load; your distributor price may differ.

AVAILABLE PACK SIZES

ITEM NO.	PACK SIZE	DOT
01633-D5505	55 gal drum	Not regulated
01633-P5010	5 gal pail	Not regulated
01633-C4201	4 × 1 gal	Not regulated
01633-B1201	1 gal bottle	Not regulated
01633-C3004	12 × 1 qt	Not regulated

PIF 01633 · TDS rev03 · Issued October 20, 2026 · Supersedes rev02

Read the product label and Safety Data Sheet before use. Orders: 800-752-6627 · sales@kor-chem.com

SCAN FOR SDS
kor-chem.com/sds

KOR-CHEM
ATLANTA, GEORGIA 30336
MAIN OFFICE: 404-344-9580
E-MAIL: sales@kor-chem.com
WEB: www.kor-chem.com

Information contained herein, is to the best of our knowledge, true and accurate, but all recommendations or suggestions are made without guarantee. Since the conditions of use are beyond our control, Kor-Chem Inc. disclaims any liability in connection with the use of our products and information contained herein. No person is authorized to make any statement or recommendation not contained herein, and any such statement or recommendation made shall not bind Kor-Chem Inc. Nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use, and no license implied or in fact is granted herein under the claims of any patent.

PC-175

WHERE IT FITS IN THE RECLAIM PROCESS

1 INK REMOVAL — **PC-175 (this product)** › **2 EMULSION REMOVAL** — ER-160 · ER-190 · ER-1-2-5 › **3 STAIN REMOVAL (HAZE)** — GIR-4U Plus · Pink Scrub · Bio-1 › **4 DEGREASE** — DG-520 · ProClean · Bio-1

TYPICAL PRODUCT CHARACTERISTICS

Appearance	Colorless, clear liquid	**Flash point**	117°F (47°C)
Odor	Citrus and acetate	**VOC**	100% by weight (935 g/L)
pH	Not applicable (solvent)	**Evaporation rate**	<1 (n-butyl acetate = 1)
Specific gravity	0.935	**Solubility in water**	Appreciable
Weight, per U.S. gallon	7.8 lb	**Stability**	Stable

SAFETY & HANDLING

HAZARDS (GHS)

- Flammable liquid and vapor (H226)
- Causes skin irritation (H315)
- May cause an allergic skin reaction (H317)
- Causes serious eye irritation (H319)
- May cause drowsiness or dizziness (H336)
- Toxic to aquatic life with long-lasting effects (H411)

FIRST AID

- **If swallowed:** Do NOT induce vomiting. Immediately call a poison center or doctor. Rinse mouth.
- **If on skin or hair:** Remove contaminated clothing. Wash with soap and water. Get medical attention if irritation or rash develops.
- **If inhaled:** Move to fresh air and keep at rest. Call a poison center or doctor if you feel unwell.
- **If in eyes:** Flush with water for at least 15 minutes, holding eyelids open. Remove contact lenses. Get medical attention if irritation persists.

PROTECTIVE EQUIPMENT

- **Eyes:** Safety glasses with side shields or splash-proof goggles; face shield if splashing is possible.
- **Hands & body:** Chemical-resistant (impervious) gloves and boots; apron for large amounts.
- **Breathing:** Use in a well-ventilated area. NIOSH-approved organic vapor respirator if the PEL is exceeded, vapors cause irritation or mists are generated.

STORAGE & DISPOSAL

- **Shelf life:** 1 year minimum at 75°F in the original closed container.
- Keep from freezing.
- **Lot number:** bottom right corner of every label, a Julian date followed by the item number.
- Keep away from heat, flame and sunlight; keep cool. Keep tightly closed in a well-ventilated place, locked up, away from strong oxidizers and acids.
- **Disposal:** Do not dump into sewers, on the ground or into waterways. Dispose of per federal, state and local regulations. Waste may be RCRA D001 (ignitable).

Safety information summarized from the PC-175 Safety Data Sheet. The SDS governs; see it for full precautions.

REGISTRATIONS & COMPLIANCE

GHS signal word	WARNING
VOC	100% by weight (935 g/L)
California SCAQMD Rule 1171	Not compliant
California Prop 65	Contains no listed chemicals
DOT, ground	Combustible liquid: not regulated in containers of 119 gal or less (49 CFR 173.150(f)); UN1993, 3, PG III at 120 gal or more.
Air and vessel	IATA / IMDG: UN1993, 3, PG III

ORDERING & SUPPORT

- **Orders:** 800-752-6627 · sales@kor-chem.com · shop.kor-chem.com
- **SDS:** scan the code below or visit kor-chem.com/sds
- **Find a distributor:** kor-chem.com/distributor-locator
- **Technical service:** our screen printing team can help match PC-175 to your inks and press-side clean-up.
- **Next step:** after printing, clean the screen with a Kor-Chem ink degradent (Bio-1, Bio-4, Bio-11).
- **Equipment:** Kor-Chem also supplies dip tanks, spray guns, scrub pads and InPro TigerClean automatic screen reclaiming systems.
- **Made in Atlanta:** manufactured by Kor-Chem, Inc., Atlanta, Georgia.

PIF 01633 · TDS rev03 · Issued October 20, 2026 · Supersedes rev02

Read the product label and Safety Data Sheet before use. Orders: 800-752-6627 · sales@kor-chem.com

SCAN FOR SDS
kor-chem.com/sds

KOR-CHEM
ATLANTA, GEORGIA 30336
MAIN OFFICE: 404-344-9580
E-MAIL: sales@kor-chem.com
WEB: www.kor-chem.com

Information contained herein, is to the best of our knowledge, true and accurate, but all recommendations or suggestions are made without guarantee. Since the conditions of use are beyond our control, Kor-Chem Inc. disclaims any liability in connection with the use of our products and information contained herein. No person is authorized to make any statement or recommendation not contained herein, and any such statement or recommendation made shall not bind Kor-Chem Inc. Nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use, and no license implied or in fact is granted herein under the claims of any patent.