PIF 09519

# PRESS WASH 5050

## FAST-ACTING SCREEN WASH

UP TO **1,024**

SCREENS PER GALLON · 0.125 FL OZ EACH

Use as supplied | 0% VOC | Fast evaporating

Textile Printing | Graphics Printing | Manual



## DESCRIPTION

Press Wash 5050 is a fast-acting screen wash for quick, easy removal of all types of ink. Its penetrants and solvents lift and remove ink without affecting screen emulsions or tape adhesion. Press Wash 5050 is highly flammable; use it only with good ventilation, away from all ignition sources.

## ADVANTAGES

**High Solvency**
Lifts and removes all types of ink

**Stencil & Tape Safe**
Does not affect emulsions or tape adhesion

**Fast Evaporating**
Evaporation rate above 1 (n-butyl acetate = 1)

**Economical**
$0.11 per screen at 0.5 fl oz (drum MSRP)

## DIRECTIONS

- Spray or wipe the affected area on the ink side of the screen, as supplied.
- Keep wiping, turning the towel often, until the area is dry.
- Before resuming printing, test print on scrap material to make sure all residue is gone.
- Highly flammable: keep away from heat, sparks and open flame; no smoking. Use explosion-proof equipment and non-sparking tools; ground and bond containers.
- Use only in a well-ventilated area.




**55 gal drum**
09519-D5507




**5 gal pail**
09519-P5008

## COST PER SCREEN

| FL OZ PER SCREEN | SCREENS PER GAL | SCREENS PER DRUM | COST PER SCREEN |
|---|---|---|---|
| 0.125 fl oz | 1,024 | 56,320 | $0.03 |
| 0.25 fl oz | 512 | 28,160 | $0.05 |
| 0.5 fl oz (reference) | 256 | 14,080 | $0.11 |

Reference use: 0.5 fl oz per screen, about 15 trigger sprays at 1 ml per spray, for $0.11 per screen. Cost = fl oz used × $0.21 per fl oz ($27.42/gal, 55 gal drum MSRP, effective July 3, 2026). Actual use varies with screen size and ink load; your distributor price may differ.

## AVAILABLE PACK SIZES

| ITEM NO. | PACK SIZE | DOT |
|---|---|---|
| 09519-D5507 | 55 gal drum | UN1993, 3, PG II |
| 09519-P5008 | 5 gal pail | UN1993, 3, PG II |

**PIF 09519 · TDS rev04 · Issued October 20, 2026 · Supersedes rev03**

Read the product label and Safety Data Sheet before use. Orders: 800-752-6627 · sales@kor-chem.com

SCAN FOR SDS
kor-chem.com/sds

KOR-CHEM
ATLANTA, GEORGIA 30336
MAIN OFFICE: 404-344-9580
E-MAIL: sales@kor-chem.com
WEB: www.kor-chem.com

Information contained herein, is to the best of our knowledge, true and accurate, but all recommendations or suggestions are made without guarantee. Since the conditions of use are beyond our control, Kor-Chem Inc. disclaims any liability in connection with the use of our products and information contained herein. No person is authorized to make any statement or recommendation not contained herein, and any such statement or recommendation made shall not bind Kor-Chem Inc. Nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use, and no license implied or in fact is granted herein under the claims of any patent.

# PRESS WASH 5050

## WHERE IT FITS IN THE RECLAIM PROCESS

**1 INK REMOVAL** — Press Wash 5050 (this product) ›

**2 EMULSION REMOVAL** — ER-160 · ER-190 · ER-1-2-5 ›

**3 STAIN REMOVAL (HAZE)** — GIR-4U Plus · Pink Scrub · Bio-1 ›

**4 DEGREASE** — DG-520 · ProClean · Bio-1

## TYPICAL PRODUCT CHARACTERISTICS

| | | | |
|---|---|---|---|
| **Appearance** | Colorless, clear liquid | **Flash point** | -4°F (-20°C) |
| **Odor** | Pungent, sweetish | **VOC** | 0% (acetone and t-butyl acetate are VOC-exempt) |
| **pH** | Not applicable (solvent) | **Evaporation rate** | >1 (n-butyl acetate = 1) |
| **Specific gravity** | 0.839 | **Solubility in water** | Soluble |
| **Weight, per U.S. gallon** | 7.0 lb | **Stability** | Stable |

## SAFETY & HANDLING

### HAZARDS (GHS)

- Highly flammable liquid and vapor (H225)
- May cause an allergic skin reaction (H317)
- Causes serious eye irritation (H319)
- May cause respiratory irritation (H335)

### FIRST AID

- **If swallowed:** Do NOT induce vomiting. Call a physician immediately. Never give anything by mouth to an unconscious person.
- **If on skin or hair:** Wash with soap and water. Remove contaminated clothing and launder before reuse. Get medical attention if irritation persists.
- **If inhaled:** Move to fresh air and keep at rest. Call a poison center or doctor if you feel unwell.
- **If in eyes:** Flush with water for at least 15 minutes, holding eyelids open. Remove contact lenses. Get medical attention if irritation persists.

### PROTECTIVE EQUIPMENT

- **Eyes:** Safety glasses with side shields or splash-proof goggles.
- **Hands & body:** Chemical-resistant (impervious) gloves; normal work clothing.
- **Breathing:** Use in a well-ventilated area. NIOSH-approved respirator if the PEL is exceeded or ventilation is inadequate.

### STORAGE & DISPOSAL

- **Shelf life:** 1 year minimum at 75°F in the original closed container.
- Keep from freezing.
- **Lot number:** bottom right corner of every label, a Julian date followed by the item number.
- Keep away from heat, flame and sunlight; keep cool. Keep tightly closed in a well-ventilated place, locked up, away from strong oxidizers and acids.
- **Disposal:** Do not dump into sewers, on the ground or into waterways. Dispose of per federal, state and local regulations. Waste may be RCRA D001 (ignitable).

Safety information summarized from the Press Wash 5050 Safety Data Sheet. The SDS governs; see it for full precautions.

## REGISTRATIONS & COMPLIANCE

| | |
|---|---|
| **GHS signal word** | DANGER |
| **VOC** | 0% |
| **California SCAQMD Rule 1171** | Compliant |
| **California Prop 65** | Contains no listed chemicals |
| **DOT, ground** | UN1993, Flammable liquid, n.o.s. (tert-butyl acetate, acetone), 3, PG II. Pails and drums ship fully regulated. |
| **Air and vessel** | IATA / IMDG: UN1993, 3, PG II |

## ORDERING & SUPPORT

- **Orders:** 800-752-6627 · sales@kor-chem.com · shop.kor-chem.com
- **SDS:** scan the code below or visit kor-chem.com/sds
- **Find a distributor:** kor-chem.com/distributor-locator
- **Technical service:** our screen printing team can help you use Press Wash 5050 safely on press and set up ventilation and grounding.
- **Next step:** after printing, clean the screen with a Kor-Chem ink degradent (Bio-1, Bio-4, Bio-11).
- **Equipment:** Kor-Chem also supplies dip tanks, spray guns, scrub pads and InPro TigerClean automatic screen reclaiming systems.
- **Made in Atlanta:** manufactured by Kor-Chem, Inc., Atlanta, Georgia.

**PIF 09519 · TDS rev04 · Issued October 20, 2026 · Supersedes rev03**

Read the product label and Safety Data Sheet before use. Orders: 800-752-6627 · sales@kor-chem.com

**SCAN FOR SDS**
kor-chem.com/sds

KOR-CHEM
ATLANTA, GEORGIA 30336
MAIN OFFICE: 404-344-9580
E-MAIL: sales@kor-chem.com
WEB: www.kor-chem.com

Information contained herein, is to the best of our knowledge, true and accurate, but all recommendations or suggestions are made without guarantee. Since the conditions of use are beyond our control, Kor-Chem Inc. disclaims any liability in connection with the use of our products and information contained herein. No person is authorized to make any statement or recommendation not contained herein, and any such statement or recommendation made shall not bind Kor-Chem Inc. Nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use, and no license implied or in fact is granted herein under the claims of any patent.