PIF 01640

PROWASH

PRESS & SCREEN WASH

LOW VOC

10%

VOC BY WEIGHT

Use as supplied | 10% VOC | Slight citrus odor

Textile Printing | Manual

DESCRIPTION

ProWash opens dried or clogged images on the screen during the production run, without harming the emulsion. Use it on textile inks for press-side wash-up, color changes and as a pre-step to color changes, and to clean squeegees and flood bars. ProWash rinses with water, is drain safe and has a slight citrus odor with no harsh solvent smell.

ADVANTAGES

Fast Acting
Opens dried or clogged images on press

Emulsion Safe
Cleans textile inks without harming the stencil

Low VOC
10% VOC by weight

Rinses With Water
Drain safe; slight citrus, no harsh solvent odor

DIRECTIONS

- Spray or wipe the affected area on the ink side of the screen, as supplied.
- Keep wiping, turning the towel often, until the area is dry.
- Before resuming printing, test print on scrap material to make sure all residue is gone.
- For squeegees and flood bars, wipe or wash the ink off with ProWash, then dry.
- Use in a well-ventilated area away from heat, sparks and flame. Ground and bond containers when transferring from drums or pails.



55 gal drum
01640-D5505



5 gal pail
01640-P5010



1 gal · 4 × 1 gal
B1201 · C4201



12 × 1 qt
01640-C3004

COST PER SCREEN

FL OZ PER SCREEN	SCREENS PER GAL	SCREENS PER DRUM	COST PER SCREEN
0.125 fl oz	1,024	56,320	$0.03
0.25 fl oz	512	28,160	$0.06
0.5 fl oz (reference)	256	14,080	$0.12

Reference use: 0.5 fl oz per screen, about 15 trigger sprays at 1 ml per spray, for $0.12 per screen. Cost = fl oz used × $0.24 per fl oz ($30.12/gal, 55 gal drum MSRP, effective July 3, 2026). Actual use varies with screen size and ink load; your distributor price may differ.

AVAILABLE PACK SIZES

ITEM NO.	PACK SIZE	DOT
01640-D5505	55 gal drum	Not regulated
01640-P5010	5 gal pail	Not regulated
01640-C4201	4 × 1 gal	Not regulated
01640-B1201	1 gal bottle	Not regulated
01640-C3004	12 × 1 qt	Not regulated

PIF 01640 · TDS rev03 · Issued October 20, 2026 · Supersedes rev02

Read the product label and Safety Data Sheet before use. Orders: 800-752-6627 · sales@kor-chem.com

SCAN FOR SDS
kor-chem.com/sds

KOR-CHEM
ATLANTA, GEORGIA 30336
MAIN OFFICE: 404-344-9580
E-MAIL: sales@kor-chem.com
WEB: www.kor-chem.com

Information contained herein, is to the best of our knowledge, true and accurate, but all recommendations or suggestions are made without guarantee. Since the conditions of use are beyond our control, Kor-Chem Inc. disclaims any liability in connection with the use of our products and information contained herein. No person is authorized to make any statement or recommendation not contained herein, and any such statement or recommendation made shall not bind Kor-Chem Inc. Nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use, and no license implied or in fact is granted herein under the claims of any patent.

PROWASH

WHERE IT FITS IN THE RECLAIM PROCESS

1 INK REMOVAL — ProWash (this product) › **2 EMULSION REMOVAL** — ER-160 · ER-190 · ER-1-2-5 › **3 STAIN REMOVAL (HAZE)** — GIR-4U Plus · Pink Scrub · Bio-1 › **4 DEGREASE** — DG-520 · ProClean · Bio-1

TYPICAL PRODUCT CHARACTERISTICS

Appearance	Colorless, clear liquid	**Flash point**	Above 113°F (45°C)
Odor	Slight citrus	**VOC**	10% by weight (about 83 g/L)
pH	Not applicable (solvent)	**Evaporation rate**	<1 (n-butyl acetate = 1)
Specific gravity	0.830	**Solubility in water**	Insoluble
Weight, per U.S. gallon	6.9 lb	**Stability**	Stable

SAFETY & HANDLING

HAZARDS (GHS)

- Flammable liquid and vapor (H226)
- Causes skin irritation (H315)
- May cause an allergic skin reaction (H317)
- Causes serious eye irritation (H319)
- May cause drowsiness or dizziness (H336)
- Toxic to aquatic life with long-lasting effects (H411)

FIRST AID

- **If swallowed:** Immediately call a poison center or doctor (aspiration hazard). Do NOT induce vomiting. Rinse mouth.
- **If on skin or hair:** Rinse off skin, then wash with soap and water. Remove contaminated clothing. Get medical attention if irritation or rash develops.
- **If inhaled:** Move to fresh air and keep at rest. Call a poison center or doctor if you feel unwell.
- **If in eyes:** Flush with water for at least 15 minutes, holding eyelids open. Remove contact lenses. Get medical attention if irritation persists.

PROTECTIVE EQUIPMENT

- **Eyes:** Safety glasses with side shields or splash-proof goggles; face shield if splashing is possible.
- **Hands & body:** Chemical-resistant (impervious) gloves and boots; apron for large amounts.
- **Breathing:** Use in a well-ventilated area. NIOSH-approved organic vapor respirator if the PEL is exceeded or vapors cause irritation.

STORAGE & DISPOSAL

- **Shelf life:** 1 year minimum at 75°F in the original closed container.
- Keep from freezing.
- **Lot number:** bottom right corner of every label, a Julian date followed by the item number.
- Keep away from heat, flame and sunlight; keep cool. Keep tightly closed in a well-ventilated place, locked up, away from strong oxidizers and acids.
- **Disposal:** Do not dump into sewers, on the ground or into waterways. Dispose of per federal, state and local regulations. Waste may be RCRA D001 (ignitable).

Safety information summarized from the ProWash Safety Data Sheet. The SDS governs; see it for full precautions.

REGISTRATIONS & COMPLIANCE

GHS signal word	WARNING
VOC	10% by weight (about 83 g/L)
California SCAQMD Rule 1171	Compliant
California Prop 65	Contains no listed chemicals
DOT, ground	Combustible liquid: not regulated in containers of 119 gal or less (49 CFR 173.150(f)); UN1993, 3, PG III at 120 gal or more.
Air and vessel	IATA / IMDG: UN1993, 3, PG III

ORDERING & SUPPORT

- **Orders:** 800-752-6627 · sales@kor-chem.com · shop.kor-chem.com
- **SDS:** scan the code below or visit kor-chem.com/sds
- **Find a distributor:** kor-chem.com/distributor-locator
- **Technical service:** our screen printing team can help set up ProWash for press-side, squeegee and flood bar cleaning.
- **Next step:** after printing, clean the screen with a Kor-Chem ink degradent (Bio-1, Bio-4, Bio-11).
- **Equipment:** Kor-Chem also supplies dip tanks, spray guns, scrub pads and InPro TigerClean automatic screen reclaiming systems.
- **Made in Atlanta:** manufactured by Kor-Chem, Inc., Atlanta, Georgia.

PIF 01640 · TDS rev03 · Issued October 20, 2026 · Supersedes rev02

Read the product label and Safety Data Sheet before use. Orders: 800-752-6627 · sales@kor-chem.com

SCAN FOR SDS
kor-chem.com/sds

KOR-CHEM
ATLANTA, GEORGIA 30336
MAIN OFFICE: 404-344-9580
E-MAIL: sales@kor-chem.com
WEB: www.kor-chem.com

Information contained herein, is to the best of our knowledge, true and accurate, but all recommendations or suggestions are made without guarantee. Since the conditions of use are beyond our control, Kor-Chem Inc. disclaims any liability in connection with the use of our products and information contained herein. No person is authorized to make any statement or recommendation not contained herein, and any such statement or recommendation made shall not bind Kor-Chem Inc. Nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use, and no license implied or in fact is granted herein under the claims of any patent.