PIF 01641

# SS INK WASH

## RECIRCULATING SCREEN & SQUEEGEE WASH

UP TO **1,024**

SCREENS PER GALLON · 0.125 FL OZ EACH

Recirculating | Non-foaming | Slow evaporating

Textile Printing | Graphics Printing | Manual



## DESCRIPTION

SS Ink Wash is a versatile ink remover for plastisol, vinyl and conventional inks, made for recirculating screen and squeegee washing machines. Its slow-evaporating formula helps extend product life in the machine. It also works as a sink ink wash, a press wash for color changes and a screen opener.

## ADVANTAGES

**Recirculating**
Reuse until heavily soiled; filter and top up

**Non-Foaming**
Made for screen and squeegee washers

**Slow Evaporating**
Helps extend product life in the machine

**Multiple Uses**
Ink wash, press wash and screen opener

## DIRECTIONS

- Recirculating cleaner: card excess ink off first. Recirculate until the product is too heavily soiled; filter and reuse, adding fresh product as needed.
- Ink wash-out: apply to the ink side, agitate both sides with a non-abrasive brush or pad, then high-pressure rinse from the bottom up.
- Press wash and screen opener: spray or wipe the area on both sides, turning the towel often until dry. Test print before resuming.
- Wear gloves and eye protection; use with good ventilation, away from heat and flame.




**55 gal drum**
01641-D5505




**5 gal pail**
01641-P5010




**1 gal · 4 × 1 gal**
B1201 · C4201

## COST PER SCREEN

| FL OZ PER SCREEN | SCREENS PER GAL | SCREENS PER DRUM | COST PER SCREEN |
|---|---|---|---|
| 0.125 fl oz | 1,024 | 56,320 | $0.04 |
| 0.25 fl oz | 512 | 28,160 | $0.09 |
| 0.5 fl oz (reference) | 256 | 14,080 | $0.17 |
| 1 fl oz | 128 | 7,040 | $0.34 |

Reference use: 0.5 fl oz per screen, about 15 trigger sprays at 1 ml per spray, for $0.17 per screen. Cost = fl oz used × $0.34 per fl oz ($43.72/gal, 55 gal drum MSRP, effective July 3, 2026). Actual use varies with screen size and ink load; your distributor price may differ.

## AVAILABLE PACK SIZES

| ITEM NO. | PACK SIZE | DOT |
|---|---|---|
| 01641-D5505 | 55 gal drum | Not regulated |
| 01641-P5010 | 5 gal pail | Not regulated |
| 01641-C4201 | 4 × 1 gal | Not regulated |
| 01641-B1201 | 1 gal bottle | Not regulated |

**PIF 01641 · TDS rev02 · Issued October 19, 2026 · Supersedes rev01**

Read the product label and Safety Data Sheet before use. Orders: 800-752-6627 · sales@kor-chem.com

SCAN FOR SDS
kor-chem.com/sds

KOR-CHEM
ATLANTA, GEORGIA 30336
MAIN OFFICE: 404-344-9580
E-MAIL: sales@kor-chem.com
WEB: www.kor-chem.com

Information contained herein, is to the best of our knowledge, true and accurate, but all recommendations or suggestions are made without guarantee. Since the conditions of use are beyond our control, Kor-Chem Inc. disclaims any liability in connection with the use of our products and information contained herein. No person is authorized to make any statement or recommendation not contained herein, and any such statement or recommendation made shall not bind Kor-Chem Inc. Nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use, and no license implied or in fact is granted herein under the claims of any patent.

# SS INK WASH

## WHERE IT FITS IN THE RECLAIM PROCESS

**1 INK REMOVAL**
**SS Ink Wash (this product)**

› **2 EMULSION REMOVAL**
ER-160 · ER-190 · ER-1-2-5

› **3 STAIN REMOVAL (HAZE)**
GIR-4U Plus · Pink Scrub · Bio-1

› **4 DEGREASE**
DG-520 · ProClean · Bio-1

## TYPICAL PRODUCT CHARACTERISTICS

| | | | |
|---|---|---|---|
| **Appearance** | Colorless, clear liquid | **Flash point** | 167°F (75°C) |
| **Odor** | Solvent | **VOC** | 100% by weight (about 950 g/L) |
| **pH** | Not applicable (solvent) | **Evaporation rate** | <1 (n-butyl acetate = 1) |
| **Specific gravity** | 0.950 | **Solubility in water** | Dispersible |
| **Weight, per U.S. gallon** | 7.9 lb | **Stability** | Stable |

## SAFETY & HANDLING

### HAZARDS (GHS)

- Combustible liquid (H227)
- Causes skin irritation (H315)

### FIRST AID

- **If swallowed:** Do NOT induce vomiting. Call a physician immediately. Never give anything by mouth to an unconscious person.
- **If on skin or hair:** Wash with soap and water. Remove contaminated clothing and launder before reuse. Get medical attention if irritation persists.
- **If inhaled:** If symptoms develop, move to fresh air. If breathing is difficult, a trained person should give oxygen; call a physician.
- **If in eyes:** Flush with water for at least 15 minutes, holding eyelids open. Remove contact lenses. Get medical attention if irritation persists.

### PROTECTIVE EQUIPMENT

- **Eyes:** Safety glasses with side shields or splash-proof goggles.
- **Hands & body:** Chemical-resistant (impervious) gloves and boots; normal work clothing.
- **Breathing:** Use in a well-ventilated area. NIOSH-approved organic vapor respirator if the PEL is exceeded or vapors cause irritation.

### STORAGE & DISPOSAL

- **Shelf life:** 1 year minimum at 75°F in the original closed container.
- Keep from freezing.
- **Lot number:** bottom right corner of every label, a Julian date followed by the item number.
- Keep away from heat, flame and sunlight; keep cool. Keep container closed in a well-ventilated place, away from strong oxidizers.
- **Disposal:** Do not dump into sewers, on the ground or into waterways. Dispose of per federal, state and local regulations.

Safety information summarized from the SS Ink Wash Safety Data Sheet. The SDS governs; see it for full precautions.

## REGISTRATIONS & COMPLIANCE

| | |
|---|---|
| **GHS signal word** | WARNING |
| **VOC** | 100% by weight (about 950 g/L) |
| **California SCAQMD Rule 1171** | Not compliant |
| **California Prop 65** | Contains no listed chemicals |
| **DOT, ground** | Combustible liquid: not regulated in containers of 119 gal or less (49 CFR 173.150(f)); NA1993, PG III at 120 gal or more. |
| **Air and vessel** | IATA / IMDG: not regulated (flash point above 140°F) |

## ORDERING & SUPPORT

- **Orders:** 800-752-6627 · sales@kor-chem.com · shop.kor-chem.com
- **SDS:** scan the code below or visit kor-chem.com/sds
- **Find a distributor:** kor-chem.com/distributor-locator
- **Technical service:** our screen printing team can help set up SS Ink Wash in your recirculating screen or squeegee washer.
- **Next step:** after ink removal, remove the stencil with a Kor-Chem emulsion remover (ER-160, ER-190, ER-1-2-5).
- **Equipment:** Kor-Chem also supplies dip tanks, spray guns, scrub pads and InPro TigerClean automatic screen reclaiming systems.
- **Made in Atlanta:** manufactured by Kor-Chem, Inc., Atlanta, Georgia.

**PIF 01641 · TDS rev02 · Issued October 19, 2026 · Supersedes rev01**

Read the product label and Safety Data Sheet before use. Orders: 800-752-6627 · sales@kor-chem.com

**SCAN FOR SDS**
kor-chem.com/sds

KOR-CHEM
ATLANTA, GEORGIA 30336
MAIN OFFICE: 404-344-9580
E-MAIL: sales@kor-chem.com
WEB: www.kor-chem.com

Information contained herein, is to the best of our knowledge, true and accurate, but all recommendations or suggestions are made without guarantee. Since the conditions of use are beyond our control, Kor-Chem Inc. disclaims any liability in connection with the use of our products and information contained herein. No person is authorized to make any statement or recommendation not contained herein, and any such statement or recommendation made shall not bind Kor-Chem Inc. Nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use, and no license implied or in fact is granted herein under the claims of any patent.