PIF 02512

SHOP MAGIC

HEAVY-DUTY ALKALINE CONCRETE FLOOR CLEANER

DILUTES UP TO **1:35** WITH WATER

pH 13 | 1:10 – 1:35 | Very low foam

Hard floors | Vehicle

DESCRIPTION

Shop Magic is a heavy-duty, concentrated alkaline cleaner that removes grease, oil, fats, carbon, wax, ink, tar, asphalt and other stubborn soils from concrete, masonry, stone and tile. It is a very low foamer designed for auto-scrubbers and related equipment. Shop Magic is not designed for composition floors, aluminum or glass.

ADVANTAGES

Concentrated & Heavy Duty
Industrial detergent; dilutes up to 1:35

Non-Acid Cleaner
Alkaline formula removes grease, oil and tar

Very Low Foaming
Built for auto-scrubbers and related equipment

Free Rinsing
Rinses freely; contains biodegradable surfactants

DIRECTIONS

1. Dilute Shop Magic with warm or hot water for best results, following the dilution guide.
2. Apply the solution with an auto-scrubber, mop, brush, sponge or pump-up sprayer.
3. If necessary, agitate to help remove heavy soils.
4. Rinse thoroughly with clear water as needed. Allow the area to dry before foot traffic resumes.
5. Not designed for composition floors, aluminum or glass.



DILUTION GUIDE

SOIL LEVEL	RATIO	APPROX. OZ/GAL	USE SOLUTION PER GAL
Very heavy	1:10	11.6	11 gal
Heavy	1:15	8	16 gal
Medium	1:20	6.1	21 gal
Light	1:35	3.6	36 gal

Ratios from the directions above; 1:X means 1 part Shop Magic to X parts water. Ounces per gallon = 128 ÷ (X + 1), rounded; yield = gallons of use solution from 1 gal of concentrate.

AVAILABLE PACK SIZES

ITEM NO.	PACK SIZE	DOT
02512-D5505	55 gal	Not regulated
02512-P5004	5 gal	Not regulated
02512-C4001	4 × 1 gal	Not regulated

PIF 02512 · TDS rev07 · Issued October 2026 · Supersedes rev06

Read the product label and Safety Data Sheet before use. Order: 800-752-6627 · sales@kor-chem.com

SCAN FOR SDS
kor-chem.com/sds

KOR-CHEM
ATLANTA, GEORGIA 30336
PHONE: 404-344-9580
E-MAIL: sales@kor-chem.com
WEB: www.kor-chem.com

Information contained herein, is to the best of our knowledge, true and accurate, but all recommendations or suggestions are made without guarantee. Since the conditions of use are beyond our control, Kor-Chem Inc. disclaims any liability in connection with the use of our products and information contained herein. No person is authorized to make any statement or recommendation not contained herein, and any such statement or recommendation made shall not bind Kor-Chem Inc. Nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use, and no license implied or in fact is granted herein under the claims of any patent.

SHOP MAGIC

TYPICAL PRODUCT CHARACTERISTICS

Appearance	Purple, clear liquid	**Flashpoint**	192°F (89°C), closed cup; Class IIIA combustible
Scent	Butyl	**Solubility**	Complete in water
pH	13	**VOC**	7%
Specific Gravity	1.040	**Foam**	Very low
Weight, per U.S. gallon	8.7 lbs	**Rinsability**	Excellent
Viscosity	Water thin	**Max. Dilution Ratio**	1:35 with water

SAFETY & HANDLING

HAZARDS (GHS)

WARNING

- Causes serious eye irritation (H319)
- Causes skin irritation (H315)
- May cause drowsiness or dizziness (H336)
- Combustible liquid (H227)

FIRST AID

- **If in eyes:** Flush with water for at least 15 minutes, holding eyelids open. Remove contact lenses. Get medical attention if irritation persists.
- **If on skin:** Wash with soap and water. Launder contaminated clothing before reuse. Get medical attention if irritation persists.
- **If swallowed:** Do NOT induce vomiting. If fully conscious, rinse mouth and drink 8 oz of water. Call a physician immediately.
- **If inhaled:** If symptoms develop, move to fresh air.

PROTECTIVE EQUIPMENT

- **Eyes:** Safety glasses with side shields or splash-proof goggles
- **Hands & body:** Chemical-resistant gloves; normal materials-handling clothing
- **Breathing:** NIOSH-approved protection if PEL is exceeded or vapors cause irritation

STORAGE & DISPOSAL

- **Shelf life:** 1 year minimum at 75°F in the original closed container.
- Keep from freezing.
- **Lot number:** bottom right corner of every label, a Julian date followed by the item number.
- Keep away from heat, flame or sunlight. Keep container tightly closed; store locked up in a well-ventilated place.
- Store away from oxidizers, acids, alkalis, chlorine, organic amines, and aluminum, zinc, tin, copper and their alloys. Do not cut, weld or torch on or near containers, even empty.
- **Disposal:** Do not dump into sewers, on the ground or into any body of water. Dispose of contents and container per federal, state and local regulations. Emptied containers retain residue; follow label warnings.

Safety information summarized from the Shop Magic Safety Data Sheet. The SDS governs; see it for full precautions.

RECOMMENDED APPLICATIONS

- Concrete
- Brick
- Masonry
- Terrazzo
- Stone
- Slate
- Ceramic Tile

PIF 02512 · TDS rev07 · Issued October 2026 · Supersedes rev06

Read the product label and Safety Data Sheet before use. Order: 800-752-6627 · sales@kor-chem.com

SCAN FOR SDS
kor-chem.com/sds

KOR-CHEM
ATLANTA, GEORGIA 30336
PHONE: 404-344-9580
E-MAIL: sales@kor-chem.com
WEB: www.kor-chem.com

Information contained herein, is to the best of our knowledge, true and accurate, but all recommendations or suggestions are made without guarantee. Since the conditions of use are beyond our control, Kor-Chem Inc. disclaims any liability in connection with the use of our products and information contained herein. No person is authorized to make any statement or recommendation not contained herein, and any such statement or recommendation made shall not bind Kor-Chem Inc. Nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use, and no license implied or in fact is granted herein under the claims of any patent.

SHOP MAGIC

REGISTRATIONS & COMPLIANCE

VOC	7%
GHS signal word	WARNING
DOT, all pack sizes	Not regulated (combustible liquid, flash point 192°F; not regulated in containers of 119 gal or less, 49 CFR 173.150(f))

ORDERING & SUPPORT

- Order: 800-752-6627 · sales@kor-chem.com
- Phone: 404-344-9580
- SDS: scan the code below or visit kor-chem.com/sds
- Find a distributor: kor-chem.com/distributor-locator

KOR-CHEM
ATLANTA, GEORGIA 30336
PHONE: 404-344-9580
E-MAIL: sales@kor-chem.com
WEB: www.kor-chem.com

Information contained herein, is to the best of our knowledge, true and accurate, but all recommendations or suggestions are made without guarantee. Since the conditions of use are beyond our control, Kor-Chem Inc. disclaims any liability in connection with the use of our products and information contained herein. No person is authorized to make any statement or recommendation not contained herein, and any such statement or recommendation made shall not bind Kor-Chem Inc. Nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use, and no license implied or in fact is granted herein under the claims of any patent.