NEW GEN CLEANING FLUIDS
TECHNICAL DATA

PRODUCT	USE	Flashpoint	Hazardous Material	Hazardous Air Pollutant (H.A.P.)	Restricted Shipping	Health			Primary Active component
						Cancer Warn-ings	CA Prop 65 Listed	TLV	
Formula TS-5	Oil, Grease, Cosmetics Screen Print Inks	None Detected	No	No	No	No	No	200 PPM	Brominated Hydrocarbon
Premium 2000	Oil, Grease Dirt, Cosmetics	None Detected	No	No	No	No	No	200 PPM	Brominated Hydrocarbon
Formula DT-1000	DTG and DTF Transfers	None Detected	No	No	No	No	No	200 PPM	Brominated Hydrocarbon
Formula TS-1	Oil, Grease Dirt, Cosmetics	None Detected	Yes	Yes	1 Gallon: **LIMITED QUANTITY** Larger Sizes: Class 6.1 UN 2810 PG III	Yes	Yes	25-300PPM	Methylene Chloride
Formula TS-3	Screen Print Inks & Adhesives	None Detected							

FORMULA TS-5

Removes grease, oil, dirt, cosmetic stains and Screen printing inks and soils from all fabrics. No Methylene Chloride or NPB

Vapor Pressure	**232mm Hg @20ºC**	**Flash Point**	**Non Detected [2]**
Specific Gravity	**1.255 (water = 1)**	**Boiling Point**	**30-42 ºC**
VOC Content:	**VOC 950 g/l**	**Evaporation Rate (n-butyl acetate =1)**	**>0.68**
Appearance:	**Clear, colorless liquid**	**Kauri-Butanol (KB Value)**	**>115**

PREMIUM 2000

Removes grease, oil, dirt, cosmetic stains and Screen printing inks and soils from all fabrics. No Methylene Chloride or NPB

Vapor Pressure	**225mm Hg @20ºC**	**Flash Point**	**Non Detected [2]**
Specific Gravity	**1.220 (water = 1)**	**Boiling Point**	**30-42 ºC**
VOC Content:	**VOC 975 g/l**	**Evaporation Rate (n-butyl acetate =1)**	**>0.64**
Appearance:	**Clear, colorless liquid**	**Kauri-Butanol (KB Value)**	**>110**

DT-1000

Removes DTF and DTG Transfers No Methylene Chloride

Vapor Pressure	**232mm Hg @20ºC**	**Flash Point**	**Non Detected [2]**
Specific Gravity	**1.255 (water = 1)**	**Boiling Point**	**30-42 ºC**
VOC Content:	**VOC 950g/l**	**Evaporation Rate (n-butyl acetate =1)**	**>0.68**
Appearance:	**Clear, colorless liquid**	**Kauri-Butanol (KB Value)**	**>115**

SHIPPING SPECIFICATIONS

PRODUCT	PACKAGE SIZE	CASE WEIGHT	DIMENSIONS	HARMANIZED TARRIF CODE
Formula TS-5	1 GAL (4x1g) 5 GAL Can 55 Gallon Drum	44lbs (20.00kg) 55lbs (24.54kg) 569lbs (258.63kg)	13" x 10.5" x 12" 12" x 12" x 15" 23" x 23"x 35"	3814.00.5090
PREMIUM 2000	1 GAL (4x1g) 5 GAL Can 55 Gallon Drum	45lbs (20.45kg) 55lbs (25.00kg) 580lbs (263.63kg)	13" x 10.5" x 12" 12" x 12" x 15" 23" x 23"x 35"	3814.00.5090
Formula DT-1000	1 GAL (4x1g) 5 GAL Can 55 Gallon Drum	44 lbs (20.45kg) 55lbs (25.00kg) 569lbs (263.63kg)	13" x 10.5" x 12" 10" x 14" x 16" 23" x 23"x 35"	3814.00.5090

TEKMAR
USA:800-564-1096
TEL: 805-965-0704
FAX: 805-963-7794
www.tekmarltd.com ●
sales@tekmarltd.com
P.O. Box 4700, Santa Barbara, CA 93140 USA

[2] Flashpoint tested using ASTM method D-56—Tag Closed Cup Test

© 2024 Technical Marketing, Ltd.